


NOELLE - BP0060 (DOWN)



ARTIKELCODE	LED KLEUR	DIAMETER	HOOGTE	BREEDTE	WATTAGE	LUMEN
BP0060-2700-40-6	● 2700K	400 mm	60 mm	40 mm	15 Watt	2025 Lm
BP0060-2700-50-6	● 2700K	500 mm	60 mm	40 mm	20 Watt	2700 Lm
BP0060-2700-60-6	● 2700K	600 mm	60 mm	40 mm	26 Watt	3510 Lm
BP0060-2700-70-6	● 2700K	700 mm	60 mm	40 mm	31 Watt	4185 Lm
BP0060-2700-80-6	● 2700K	800 mm	60 mm	40 mm	35 Watt	4725 Lm
BP0060-2700-90-6	● 2700K	900 mm	60 mm	40 mm	40 Watt	5050 Lm
BP0060-2700-100-6	● 2700K	1000 mm	60 mm	40 mm	44 Watt	5940 Lm
BP0060-2700-120-6	● 2700K	1200 mm	60 mm	40 mm	53 Watt	7155 Lm
BP0060-2700-140-6	● 2700K	1400 mm	60 mm	40 mm	62 Watt	8370 Lm
BP0060-2700-150-6	● 2700K	1500 mm	60 mm	40 mm	66 Watt	8910 Lm
BP0060-2700-160-6	● 2700K	1600 mm	60 mm	40 mm	70 Watt	9450 Lm
BP0060-2700-180-6	● 2700K	1800 mm	60 mm	40 mm	80 Watt	10800 Lm
BP0060-2700-200-6	● 2700K	2000 mm	60 mm	40 mm	90 Watt	12150 Lm
BP0060-2700-220-6	● 2700K	2200 mm	60 mm	40 mm	99 Watt	13365 Lm
BP0060-2700-240-6	● 2700K	2400 mm	60 mm	40 mm	110 Watt	14850 Lm

SPECIFICATIES LICHTBRON

Bevestiging	Pendel
Lichtbron	LED
Driver	Inclusief
Dimbaarheid	Fase afsnij
Voltage	230 VAC



OP AANVRAAG MOGELIJK

● 2700K (Standaard)

● 3000K

● 4000K

● 6500K

● Tunable white

● RGB

● RGBW

