

Technical Data Sheet

Product Description 产品类型	Range 类别	Model型号
Emergency Bulkhead Series	Maintained mode	A801/30L*2/M(Auto test)
Light Source 光源		
Rated Wattage / Lamp Cap 额定瓦数	6~7.5W	
Lumens 流明 (M需填AC和DC的流明值)	3000K(AC:389lms,DC:267lms) 4200K(AC:482lms,DC:283lms) 6000K(AC:423lms,DC:278lms)	
Light Source 光源	SMD 2835 LEDS	
Colour Temperature (K) 色温	TC=3000K/4200K/6000K	
Colour Rendering Index CRI (Ra) 显色指数	Ra=85	
Light Source Life(Hrs) 光源寿命	30000hrs	
Beam Angle 光束角	105.80° （50%Imax）	
Lamp Working Temperature 工作温度	-20℃-55℃	
Electrical 电气		
Voltage (V) 工作电压	220V	
Battery 电池	4.8V SC1800mAh Ni-Cd	
Running current (I) 工作电流	325A	
Total running Wattage (W) 实际功率	6~7.5W（满电时）	
Charging current 充电电流	93-210mA	
Discharging current 放电电流	392-578mA	
conversion voltage 转换电压	150-180V AC	
Battery alarm voltage 电池报警电压	6.5~6.9V	
Electrical Classification 电器分类	II 类	
Power Factor (PF) 功率因素	0.9PF	
General Details 细节信息		
O/all dims (mm) 产品尺寸	349*121*80mm	
Product Weight 产品净重	0.75kg	
Carton Weight 产品+内盒的重量	0.9kg	
Packaging Sizes 外箱尺寸/几个装一箱	52.4*38.5*27.8CM/ 12PCS/CTN	
Packed Weight 整箱重量	12.2KG/CTN	
Ingress Protection (IP) 防护等级	IP65	
Method of fix 安装方式	wall mounted and ceiling mounted	
Housing Material 外壳材料	Polycarbonate	
Approvals 认证		
Guarantee 保质期	3 years	
Certification 证书	CE	
Quality Assurance System 质量体系	ISO 9001	
Manufactured in accordance to 制造标准	BS EN 60598 – 2 – 22	

Please see the picture and dimension next page.

